

*Feed-tube assemblies available with
these Nelson Rotators*

APPLICATION

- Versatile, portable stake mounting option for the following Nelson Rotator sprinklers:
 - R2000WF
 - R10/R10 Turbo
- Sprinkler units perfect for the following applications:
 - Irrigation
 - Frost protection
 - Roof sprinkling for cooling
 - Cooling livestock

FEATURES

- Durable, UV, kink resistant, and flexible PVC tubing
- Fast and simple installation
- Easy nozzle cleaning - kink the tube to stop the flow
- Low cost, high value

SPECIFICATIONS

- **Rotator options:** R10/R10T, R2000WF
- **Operating range:** 1.0 - 3.1 GPM
- **Adapter:** Acme thread #9677
- **Largest nozzle:** #15 2TN - 2.5 2000FC
- **Tubing:** 10mm Flexible PVC 48" #9099-048
500' coil #9099
I.D - 0.505" / O.D - 0.355"
- **Barb:** QC LTO, 10mm Comp x Male QC #9740
QC barb x 10mm Comp #9739
- **Stake:** 36" Steel 8mm #9725-036
36" Fiberglass 8mm #10970
48" Steel 8mm #9725-048



R2000 Windfighter
Rotator


R10 Turbo
Rotator

Acme thread adapter #9677



FT5 Quick Connect
Feedtube Assembly

ROTATOR FEED-TUBE ASSEMBLY INSTALLATION INSTRUCTIONS



Punch Hole

Hand punch / drill punch tool



Insert Barb

Drill installation tool



Drive Stake

Stake Installation tool



Mount to Stake

Acme thread #9677



Attach Sprinkler

R10/R10T or R2000WF

INSTALLATION TOOLS



Accessory	Description	Part Number
Hand Punch Tool	Creates hole for barb connection - 10mm (White)	#9776
Drill Punch Tool	Creates hole for barb connection - 10 mm	#9835-001
Stake Installation Tool	Protects stake when driving into hard ground - 8mm	#10288
Drill Installation Tool	Installs QC barb	#9845

ACCESSORIES



Accessory	Description	Part Number
Plug	Plugs hole when barb is removed - Rubber (fits inside QC barb); Goof	R #9826; G #9831
Coupler	Splices tubing - 10mm	#9813
Threaded cap	Shut-off for acme adapter	#10615
Female ACME x 1/2" PVC spigot	For extending riser	#10352
1/2 spigot x comp. barb	Connects tubing to PVC	#10623